

## Lubricants – Greases

Version: EEE/06

## Valvoline™ Multipurpose Calcium 2

*Conventional calcium grease with good water resistance properties. Suitable for lubrication of machinery working in damp conditions.*

Valvoline Multipurpose Calcium 2 is a Calcium thickened lubricating grease formulated with mineral base oil and enhanced with a green color to enable easy verification on applied parts. The product protects against rust and corrosion especially in marine and agriculture applications where water resistance is needed.

### Performance levels

ISO 6743-9:	L-XBBHA 2
DIN 51502:	K2E-25

### Applications

Suitable for use in normal temperature conditions.

Suitable for several construction, agricultural and marine applications.

Suitable for marine equipment like: deck machine, winches, gearboxes.

Suitable for conditions where good lubrication in the presence of moisture and dust is specially required.

### Features & Benefits

#### Good protection

Valvoline Multipurpose Calcium 2 protects against rust and corrosion. Very high resistance to washout effect of water and moisture.

#### Good performance

The product lubricates and protects under severe circumstances like damp and wet conditions. In the presence of water, a good lubricating film will be maintained, avoiding wash out. Excellent mechanical and colloidal stability.

#### Multipurpose applications

Valvoline Multipurpose Calcium 2 was developed for universal lubrication of several mechanical equipment working in wet circumstances.

#### Severe working conditions

The product can even be used in unfavorable working conditions like canal building or swamp lumbering or on-surface mining.

# PRODUCT INFORMATION



## Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit [www.valvolineeurope.com](http://www.valvolineeurope.com)

## Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Multipurpose Calcium 2	
NLGI grade	2
Soap type	Calcium
Colour	Green
Texture	Tacky
Density @ 20°C	0.90
Application temperature °C	-25 to + 80
Dropping Point, °C ISO 2176	115
Oil Viscosity, mm <sup>2</sup> /s @ 40°C ISO 3104	100
Oil Viscosity, mm <sup>2</sup> /s @100°C ISO 3104	10,5
Water washout, rating @ 40°C DIN 51807/1	1

## This information only applies to products manufactured by:

Ellis Enterprises East doo Kruševac  
Mike Stojanovića 15, Kruševac  
Registration nr: 21368997 / TIN: 110618744

™ Trademark of Valvoline, registered in various countries ©

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises East doo Kruševac and its affiliates assume legal responsibility.

## Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <https://sds.valvoline.com/>

## Protect the environment

Take used oil and grease to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

## Storage

We recommend to store all packages under cover, protected from direct influence of sun and moisture, away from the ignition source.. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Recommended storage temperature: - 5°C to +25°C.

Replaces