

## Lubricants – Greases

Version: **EEE/02b**

# Valvoline™ Multipurpose Lithium 2

**Conventional multipurpose lithium grease suitable for use in normal temperature conditions.**

Valvoline Multipurpose Lithium 2 is a Lithium thickened lubricating grease formulated with mineral base oil. Mechanically stable and easily pumpable due to its smooth consistency.

Performance levels	
ISO 6743-9:	L- XCCHA 2
DIN 51502:	K2K-30

## Applications

Suitable for use in normal temperature conditions and in a wide range of plain and rolling bearings.

Lubrication of machine assembly blocks in all industries at moderate loads, speeds and operating temperatures.

Can be used in several industrial and automotive applications.

## Features & Benefits

### Good protection

Valvoline Multipurpose Lithium 2 protects against rust and corrosion and has good oxidation stability properties.

The grease is mechanical stable so that it will not be pressed out of bearings.

High degree of lubricating assembly block protection against corrosion and rust.

Good resistance to the impact of water

Good lubricating ability in conditions of moderate loads.

### Multipurpose applications

The product was developed for universal lubrication of several mechanical equipment. Its broad applicability facilitates the choice when a general grease is required.

# PRODUCT INFORMATION



## Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit [www.valvolineeurope.com](http://www.valvolineeurope.com)

For all latest OEM specifications and approvals visit: [www.pisheets.valvoline.com](http://www.pisheets.valvoline.com)

## Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Multipurpose Lithium 2	
NLGI grade	2
Soap type	Lithium
Colour	Blue - Green
Texture	Smooth
Density @ 20°C.	0.9
Application temperature, °C	-30 to + 110
Dropping Point, °C ISO 2176	195
Oil Viscosity, mm <sup>2</sup> /s @ 40°C ISO 3104	100
Oil Viscosity, mm <sup>2</sup> /s @100°C ISO 3104	10,0
Oxidation stability, kPa @ 100h/100°C, ASTM D 942	20
Copper corrosion, degree ASTM D 4048	1a

## This information only applies to products manufactured by:

Ellis Enterprises East doo Kruševac  
Affiliate of Valvoline  
Mike Stojanovića 15, Kruševac  
Registration nr: 21368997 / TIN: 110618744

™ Trademark of Valvoline, registered in various countries ©

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises East doo Kruševac and its affiliates assume legal responsibility.

## Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <https://sds.valvoline.com/>

## Protect the environment

Take used oil or grease to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

## Storage

We recommend to store all packages under cover, protected from direct influence of sun and moisture, away from the ignition source. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Recommended storage temperature: - 5°C to +25°C.

Replaces – EEE/02a